



NBS DATA

| IFC | |
|-----------------------------------|---|
| Ifc Export As Ifc Covering Type | Ifc Export As Ifc Covering Type |
| Ifc Export Type CLADDING NBS Data | Ifc Export Type CLADDING |
| Accessories | 50 x 50 x 3000mm plastic battens, 72 x 12mm fascia boards, 54 x 40mm corner trims |
| Coefficient Of Expansion | 0.032 mm/m/°C - (-30°C to +30°C) |
| Colour Options | Oak, Walnut, Silver Ash, Slate grey and Charcoal |
| Impact Strength | 86 J/m Izod Unnotched |
| Length Options | 4.0m |
| Profile | Shiplap Cladding |
| Recyclability | 100% |
| Recycled Content | 90% (60% wood fibre and 30% HDPE) |
| Section Size | 20 x 140 mm |
| Water Absorption | 1.04% |
| Acoustic Rating | n/a |
| Combustible | TRUE |
| Finish | Brushed grain surface |
| Fire Rating | D – s1, d0 (EN 13501-1) |
| Flammability Rating | n/a |
| Fragility Rating | n/a |
| Material | wood (FSC 100%) polymer composite (WPC) |
| Reference | Pura Clad |
| Total Thickness | 20 mm |
| Has Anti Static Surface | FALSE |
| Has Non Skid Surface | TRUE |



NBS DATA

FASCIA BOARD

| IFC | |
|-----------------------------------|---|
| Ifc Export As Ifc Covering Type | Ifc Export As Ifc Covering Type |
| Ifc Export Type FLOORING NBS Data | Ifc Export Type CLADDING |
| Accessories | 50 x 50 x 3000mm plastic battens, 72 x 12mm fascia boards, 54 x 40mm corner trims |
| Coefficient Of Expansion | 0.032mm/m/°C (-30°C to +30°C) |
| Colour Options | Oak, Walnut, Silver Ash, Slate Grey, Charcoal |
| Impact Strength | 86J/mI zod Unnotched |
| Length Options | 2.7 m |
| Profile | Uniform Plank |
| Recyclability | 100% |
| Recycled Content | 90% (60% wood fibre and 30% HDPE) |
| Section Size | 72 x 12 mm |
| Water Absorption | 1.04% |
| Acoustic Rating | n/a |
| Combustible | TRUE |
| Finish | Brushed flat grain surface |
| Flammability Rating | n/a |
| Fragility Rating | n/a |
| Material | Wood (FSC 100%) polymer composite (WPC) |
| Reference | PURA SCREENS |
| Total Thickness | 12 mm |
| Has Anti Static | FALSE |
| Surface Has Non Skid | TRUE |
| Surface Technical | info@puracomposites.ie |



NBS DATA

CORNER NOSING TRIM

| IFC | |
|-----------------------------------|---|
| Ifc Export As Ifc Covering Type | Ifc Export As Ifc Covering Type |
| Ifc Export Type FLOORING NBS Data | Ifc Export Type CLADDING |
| Accessories | 50 x 50 x 3000mm plastic battens, 72 x 12mm fascia boards, 54 x 40mm corner trims |
| Coefficient Of Expansion | 0.032mm/m/°C (-30°C to +30°C) |
| Colour Options | Oak, Walnut, Silver Ash, Slate Grey, Charcoal |
| Impact Strength | 86J/mlzodUnnotched |
| Length Options | 3.0 m |
| Profile | UniformLTrim |
| Recyclability | 100% |
| Recycled Content | 90%(60%woodfibreand30%HDPE) |
| Section Size | 54 x 40 mm |
| Water Absorption | 1.04% |
| Acoustic Rating | n/a |
| Combustible | TRUE |
| Finish | Brushedflatgrainsurface |
| Flammability Rating | n/a |
| Fragility Rating | n/a |
| Material | Wood(FSC100%)polymercomposite(WPC) |
| Reference | PURATRIM |
| Total Thickness | 5 mm |
| Has AntiStatic Surface Has | FALSE |
| Non Skid Surface | TRUE |
| Technical Contact | info@puracomposites.ie |