



IFC	
Ifc Export As Ifc Covering Type	Ifc Export As Ifc Covering Type Ifc
Ifc Export Type FLOORING	Export Type Flooring
NBS DATA	
INFORMATION	DETAILS
Accessories	50 x 50mm, 100 x 50mm / 150 x 50mm / 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/end clips, 72 x 12mm fascia boards, 54 x 40mm corner trims
Coefficient Of Expansion	0.032 mm/m/°C (-30 °C to +30°C)
Colour Options	Oak, Walnut, Charcoal, Slate Grey, Silver Ash
Flexural Modulus	396 9MPa
Flexural Strength	27.4 MPa
Impact Strength	86 J/m Izod Unnotched
Length Options	3.6 or 4.0m
Profile	Reversible Grooved or Wood Grain
Recyclability	100%
Recycled Content	90% (60% wood fibre and 30% HDPE)
Section Size	25 x 135 mm
Slip Potential Value	Low potential for slip; Wet: 36 - 40 (Grain - Grooves) Dry: 52 - 51 (Grain - Grooves)
Tensile Strength	25.6MPa (ASTM D638-10)
Water Absorption	1.81%
Acoustic Rating	n/a
Combustible	TRUE
Finish	Deep grooves or Wood grain
Fire Rating	Cfl - s1 (EN 13501-1)
Flammability Rating	n/a
Fragility Rating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	Pura Deck Pro
Total Thickness	21mm
Has Anti Static Surface	FALSE
Has Non Skid Surface	TRUE
Technical Contact	info@puracomposites.ie



IFC	
Ifc Export As Ifc Covering Type	Ifc Export As Ifc Covering Type
Ifc Export Type FLOORING	Ifc Export Type Flooring
NBS DATA	
INFORMATION	DETAILS
Accessories	50 x 50mm, 100 x 50mm / 150 x 50mm / 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/end clips, 72 x 12mm fascia board
Coefficient Of	0.032 mm/m/°C (-30 °C to +30°C)
Expansion Colour	Oak, Walnut, Charcoal, Slate Grey, Silver Ash
Options	86 J/m Izod Unnotched
Impact Strength	2.2m
Length Options	Uniform L Trim
Profile	100%
Recyclability	90% (60% wood fibre and 30% HDPE)
Recycled Content	54 x 40mm
Section Size	1.81%
Water Absorption	n/a
Acoustic Rating	TRUE
Combustible	Brushed flat grain surface
Finish	n/a
Flammability Rating	n/a
Fragility Rating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	
Total Thickness	5mm
Has Anti Static Surface	FALSE
Has Non Skid Surface	TRUE
Technical Contact	info@puracomposites.ie



IFC	
Ifc Export As Ifc Covering Type	Ifc Export As Ifc Covering Type
Ifc Export Type FLOORING	Ifc Export Type Flooring
NBS DATA	
INFORMATION	DETAILS
Accessories	50 x 50mm, 100 x 50mm / 150 x 50mm / 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/end clips, 54 x 40mm corner trims
Coefficient Of Expansion	0.032 mm/m/°C (-30 °C to +30°C)
Colour Options	Oak, Walnut, Granite, Stone, White Ash
Impact Strength	86 J/m Izod Unnotched
Length Options	2.2m
Profile	Uniform Plank
Recyclability	100%
Recycled Content	90% (60% wood fibre and 30% HDPE)
Section Size	72 x 15mm
Water Absorption	1.81%
Acoustic Rating	n/a
Combustible	TRUE
Finish	Brushed flat grain surface
Flammability Rating	n/a
Fragility Rating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	PURADECK Fascia Board
Total Thickness	15mm
Has Anti Static Surface	FALSE
Has Non Skid Surface	TRUE
Technical Contact	nfo@puracomposites.ie



IFC	
Ifc Export As Ifc Covering Type	Ifc Export As Ifc Covering Type
Ifc Export Type FLOORING	Ifc Export Type Flooring
NBS DATA	
INFORMATION	DETAILS
Accessories	A2 grade steel, T15 countersunk screw (6mm head, 3mm shank, 4mm tread), 30mm metal or 35mm wood T15 drill bit
Colour Options	Black
Recyclability	100%
Recycled Content	100% HDPE
Section Size	28 x 20 x 11mm (L x W x H)
Water Absorption	0%
Acoustic Rating	n/a
Combustible	TRUE
Material	HDPE
Reference	6mm Hidden Fastener
Technical Contact	info@puracomposites.ie



IFC	
Ifc Export As Ifc Covering Type	Ifc Export As Ifc Covering Type
Ifc Export Type FLOORING	Ifc Export Type Flooring
NBS DATA	
INFORMATION	DETAILS
Accessories	A2 grade steel, T15 countersunk screw (6mm head, 3mm shank, 4mm tread), 30mm metal or 35mm wood T15 drill bit
Colour Options	Silver
Recyclability	100%
Recycled Content	0%
Section Size	45 x 30 x 10mm (L x W x H)
Water Absorption	0%
Acoustic Rating	n/a
Combustible	TRUE
Material	304 Grade Stainless Steel
Reference	3mm Hidden Fastener
Technical Contact	info@puracomposites.ie



IFC	
Ifc Export As Ifc Covering	Ifc Export As Ifc Covering
Type Ifc Export Type	Type Ifc Export Type
NBS DATA	
Flooring	
INFORMATION	DETAILS
Accessories	A2 grade steel, T15 countersunk screw (6mm head, 3mm shank, 4mm tread), 30mm metal or 35mm wood T15 drill bit
Colour Options	Black
Recyclability	100%
Recycled Content	0%
Section Size	30 x 30 x 10mm (L x W x H)
Water Absorption	0%
Acoustic Rating	n/a
Combustible	TRUE
Material	304 Grade Stainless Steel
Reference	Starter Fastener
Technical Contact	info@puracomposites.ie